



QT951

Quantec Accessible Disabled Persons Toilet Alarm Kit



Overview

A cost-effective expansion kit that adds true BS8300 compliant accessible toilet alarm functionality to a Quantec Addressable Call System.

Includes a QT607 ceiling pull unit, a QT605S reset point c/w confidence sounder, a Quantec slave overdoor light c/w sounder and an NC949 Accessible Toilet Sticker.

Allows people in distress to call for help quickly and easily.

Call acknowledgement function provides audible & visual feedback inside the WC that help is on the way (see Operation section below).

Staff can 'Accept' alarm calls at a Quantec display.

Multiple kits can be used on one Quantec system.

Includes a free MRSA resistant anti-bacterial pull cord pack (for a limited period only).

Backwards compatible.

Must be used in conjunction with at least one Quantec Controller.

Technical Specifications

Mains supply	Power derived from main QT601-2 Quantec Controller (not supplied).
Internal power supply	N/A.
Total output current limited to	N/A.
Quiescent current	Typically 6mA.
Zone current	N/A.
Alarm current	Less than 30mA (all QT951 devices).
Max battery size and type	An optional standby battery supply (2 x 12V 7Ah VRLA) can be connected at the main QT601-2 Quantec Controller, not supplied.
Auxiliary relays	N/A. However optional QT612 Relay Output Devices can be connected to the Quantec network/wiring.
Indicators	QT607 has a red Reassurance LED; QT605S has a red/green Reassurance LED; QT606S has twin red/green Alarm LEDs.
Controls	QT607 Ceiling pull activated by two pull cord bangles. QT605S has a Reset button. Call Accept function can be carried out at a Quantec Display (not supplied).
Expansion connections	N/A. However additional call and indicating devices can be connected to the Quantec network/wiring.
Onboard Sounder	Yes (on QT605S and QT606S).
Onboard Infrared Receiver	No.
Product dimensions (mm)	87 W x 87 H x 68 D (QT606S); 87 W x 87 H x 24 D (QT605S). Ceiling pull measures 93mm diameter x 27 D.
Packaging dimensions (mm)	143 W x 96 H x 102 D mm (size of QT951 kit box containing all items).
Construction & finish	Plastic.
IP Rating	IP41 (QT606S); IP40 (QT605S); IP21 (QT607).
Weight	0.30kg.
Operating conditions/temperature	-5°C to +40°C. Max relative humidity: 95%.
Notes	The QT951 is an expansion kit designed for use with Quantec Addressable Call Systems. It must be used in conjunction with at least one QT601-2 Quantec Controller.

Challenge Way, Martland Park

Wigan

T: 01942 322744 E: sales@c-tec.co.uk W: <https://www.c-tec.com>